



Def't 24 1812
I commenced a Survey of Section 29, T. 7, R. 6
for Adus Vails et al

David Rolison F.B.
John Baker } C. B.
William Geir }

L. P. Parker
Dep. Surveyor Greene County.

Var.

Course.	Point of Beginning.	Chains Distance.	Corrected Bearings.
North	SW	40.33	W 1/4
East	W 1/4	40.30	center
North	S 1/4	40.38	center
		80.78	N 1/4
East	SW	40.30	S 1/4
South	N 1/4 SW	40.36	S 1/4 SW
	center SW		

Notice of Survey

Bessie Perkins you are hereby notified that on the 24 day of September 1912 the County Surveyor will proceed to locate, relocate and perpetuate the lines and corners in the west half of the South west quarter of section 29 Township 7 north range 5 west Greene County Indiana also the South west half of the North East quarter of the South East quarter of section 30 in said county, Township and Range also 7 1/2 ac in the South west corner of the South East quarter of the South west quarter of section 29 Township 7 north Range 5 west, in Greene County, Indiana. Served 12 day September 1912
Adus Vails

CORNER ESTABLISHED.	Monument.	Device.	WITNESS POINTS OR BEARING TREES.	Mark or Dia. in Inches.	COURSE.	Links Distant.	REMARKS.
S 1/4 Reest.			Bl oak	24	S 15 1/2 E	40 feet	
center 1/4			cherry	4	N 11 W	90 feet	
N 1/4 SW			Hickory	5	S 66 W	29 1/2 feet	
W 1/4 SW			P oak	30	S 28 1/2 W	31 feet	
W 1/4			W. oak	8	S 42 W	43 1/2 feet	
W 1/4 NW SW			W oak	6	S 51 W	39 1/2 feet	
center 1/4 SW			no witness near				

Surveyed in sections 28 & 29-7-7

notice being given in the Linton Daily Citizen I commenced a survey for William E. Longly et al, in sections 28 & 29 Township 7 north Range 7 west in Greene County Indiana

courses
South from NE 29-7-7 to SE 29-7-7
West " SE 29-7-7 to SW 29-7-7
North " SW 29-7-7 to NW 29-7-7
West " NE 29-7-7 to NW 29-7-7
East " W 1/4 29-7-7 to E 1/4 29-7-7
West " E 1/4 SW to W 1/4 SW 29-7-7
East " W 1/4 28-7-7 to center 28-7-7
South " center 28-7-7 to S 1/4 28-7-7
West " S 1/4 28-7-7 to SE 29-7-7

corners Established

W 1/4 28-7-7 Stone +
E 1/4 SE 29-7-7 Stone +
SE 29-7-7 Stone +
center SW 28-7-7 Stone +
W 1/4 SW 28-7-7 Stone +
N 1/4 SW 28-7-7 Stone +
S 1/4 29-7-7 Stone +
S 1/4 SE 29-7-7 Stone +
center 29-7-7 Stone +
E 1/4 NW 1/4 29-7-7 Stone +
W 1/4 NW 1/4 29-7-7 Stone +
W 1/4 29-7-7 Stone +

This survey was for the purpose of locating the NW 1/4 of SW 1/4 28-7-7 40 a, the SE 1/4 29-7-7-160 a, all of the South half of the NW 1/4 29-7-7 80 a, 17 a, off the East side of the SE 1/4 SW 1/4 of 29-7-7 also 12 1/2 a and 11 a, in NE 1/4 SW 1/4 29-7-7

Thomas H. Rolison
County Surveyor
L. P. Parker

Sec 29-7-5 June 29 - 1946
N 1/4 NE Found Stone - W Oak 32" N 90 W 86.3 ft.
N 1/4 Found Stone

